

# ROVSKI

Rev. No:	ROVSKI INDUSTRIES SDN. BHD.	Effective Date:
1	TECHNICAL DATA SHEET	07/09/2001
		Page: 1 of 1

<b>Product</b>	<b>ROVSKI 1538</b>	
<b>Uses</b>	ROVSKI 1538 is a butyl rubber sealing tape for non-critical sealing and glazing application in automotive trim line or electrical appliances. Provides economical installation because of its form and ease of handling.	
<b>Characteristics</b>	ROVSKI 1538 has some degree of pressure sensitivity and is sufficiently soft for ease of compression during installation. It has good elongation, good weather and ageing resistance. It is permanently flexible and does not harden. It does not stain.	
<b>Properties</b>	Appearance	Black compound
	Specific Gravity (28°C)	1.00 – 1.40
	Needle Penetration @ 28°C	65 – 84
	Peel Adhesion (kgf/6mm)	0.60 – 1.20
	Tensile strength (kgf/cm <sup>2</sup> )	0.20 – 0.70
	Shear strength (kgf/1.5cm <sup>2</sup> )	0.60 – 1.20
	Elongation (%)	>1200
<b>Application</b>	ROVSKI 1538 is a ready to used tape sealer, reeled up with release paper. It is precut at a fixed length. To use it, just peel off from the release paper and apply. Area of application must dry, clean, free from dirt and oil. Application temperature: 5 °C – 40 °C.	
<b>Caution</b>	<ol style="list-style-type: none"> <li>1. Store in cool, dry and clean area.</li> <li>2. Avoid unnecessary exposure to dust.</li> <li>3. To avoid deformation of tapes, store vertically and do not put heavy objects onto tapes.</li> <li>4. Shelf life is 1 year.</li> </ol>	
<b>Dimension and Packing</b>	3mm x 3mm x 20m (sq) 3mm x 5mm x 20m (sq) 3mm x 20m (rd) 5mm x 13m (rd) 6mm x 13m (rd) 7mm x 13m (rd) 8mm x 13m (rd)  Other sizes and packing available upon request and subjected to arrangement.	

The information given above is true and is based on our own study and research work and experience. ROVSKI Industries Sdn Bhd does not provide warranty or guarantee for products made at different conditions for which are beyond our control. All separate trial cases should be studied and tested to obtain own parameter before any order and delivery.